


HG-L Lightweight & Flexible Series

Greatly decreased the product weight,
far less cost to install.

380W–400W



• Products Features

- Lightweight, Ultra-high flexibility, Easy to install.
- Reducing the adaptive loss to get higher power.
- Competitive weak light tolerance performance.
- Minimizing the shading affection to reduce power loss.
- The superior reliability has been proven through rigorous weathering test:
 - Sand and dust resistance, acid and alkali-resistance, salt mist resistance
 - Anti- PID
 - Hail shock resistance


• Quality System

ISO9001
ISO14001
ISO45001

• Product Certification






• Product Warranty



Quality and process performance Assurance



Liner power Output Warranty



Electrical Parameters

Module Type	HG-L380-54CW		HG-L385-54CW		HG-L390-54CW		HG-L395-54CW		HG-L400-54CW	
	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Maximum Power (P_{mp})	380W	283W	385W	286W	390W	290W	395W	294W	400W	298W
Open Circuit Voltage (V_{oc})	37.15V	34.55V	37.29V	34.68V	37.43V	34.81V	37.60V	34.97V	37.75V	35.12V
Short Circuit Current (I_{sc})	13.52A	10.91A	13.59A	10.97A	13.67A	11.03A	13.75A	11.10A	13.83A	11.16A
Max Power Voltage (V_{mp})	30.57V	28.97V	30.70V	29.10V	30.85V	29.24V	31.01V	29.39V	31.17V	29.54V
Max Power Current (I_{mp})	12.45A	9.77A	12.55A	9.83A	12.66A	9.92A	12.74A	10.00A	12.84A	10.09A
Module Efficiency STC (η_{stc})	19.4%		19.6%		19.9%		20.1%		20.4%	
Power Tolerance	0~+5W									
Maximum System Voltage	1500V DC									
Max Serie Fuse Rating	25A									

STC:irradiance 1000W/m² module temperature 25°C AM=1.5

NMOT: irradiance of 800W / m², ambient temperature 20°C, and wind speed 1m / s

The uncertainty of Pmax, Voc, Isc testing is ± 3%

Mechanical Specifications

External Dimension	1726mm*1137mm		
Type	Basic Version	Enhanced Version	High Performance Version
Thickness	2.7mm	3.0mm	3.2mm
Weight	6.0kg	6.8kg	8.0kg
Solar Cell	Mono crystalline182*91mm, 108 (6*18)		
Frame	/		
GLASS	/		
Junction Box	IP68,3diodes, MC4 compatible		
Output Cables	4.0mm²(IEC),300mm(+)/300mm(-)or Customized Length		

Temperature characteristic

Pmax Temperature Coefficient	-0.35 %/° C
Voc Temperature Coefficient	-0.26 %/° C
Isc Temperature Coefficient	+0.047 %/° C
Operating Temperature	-40 ~+85 ° C
Nominal module operation temperature	45 ± 2 ° C

Package

Packing Unit	40HQ	17.5m platform truck
PCS/CTNS	68	68
Qty of Package	24	36
PCS/Packages	1632	2448