


HG-L Lightweight & Flexible Series

Greatly decreased the product weight,
far less cost to install.

465W-485W



• Products Features

- Lightweight, Ultra-high flexibility, Easy to install.
- Reducing the adaptive loss to get higher power.
- Competitive weak light tolerance performance.
- Minimizing the shading affection to reduce power loss.
- The superior reliability has been proven through rigorous weathering test:
 - Sand and dust resistance, acid and alkali-resistance, salt mist resistance
 - Anti- PID
 - Hail shock resistance


• Quality System

ISO9001
ISO14001
ISO45001

• Product Certification



• Product Warranty






Quality and process performance Assurance



Liner power Output Warranty

Address: No.633 Chengnan Avenue, Banqiao Industrial Park, Rongchang District, Chongqing, China
Email: info@hg-energy-group.com
Website: <https://www.hg-energy-group.com>



Electrical Parameters

Module Type	HG-L465-66CW		HG-L470-66CW		HG-L475-66CW		HG-L480-66CW		HG-L485-66CW	
	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Maximum Power (P_{mp})	465W	346W	470W	350W	475W	353W	480W	357W	485W	361W
Open Circuit Voltage (V_{oc})	45.20V	42.18V	45.35V	42.32V	45.50V	42.46V	45.65V	42.60V	45.80V	42.70V
Short Circuit Current (I_{sc})	13.44A	10.85A	13.51A	10.90A	13.58A	10.96A	13.65A	11.02A	13.73A	11.08A
Max Power Voltage (V_{mp})	37.32V	35.37V	37.47V	35.51V	37.62V	35.66V	37.77V	35.80V	37.92V	35.90V
Max Power Current (I_{mp})	12.48A	9.78A	12.56A	9.86A	12.64A	9.90A	12.72A	9.97A	12.80A	10.06A
Module Efficiency STC (η_s)	19.5%		19.7%		19.9%		20.1%		20.4%	
Power Tolerance	0~+5W									
Maximum System Voltage	1500V DC									
Max Serise Fuse Rating	25A									

STC:irradiance 1000W/m² module temperature 25℃ AM=1.5

NMOT: irradiance of 800W / m², ambient temperature 20℃, and wind speed 1m / s

The uncertainty of Pmax, Voc, Isc testing is ± 3%

Mechanical Specifications

External Dimension	2096mm*1137mm		
Version	Basic Version	Enhanced Version	High Performance Version
Thickness	2.7mm	3.0mm	3.2mm
Weight	7.2kg	8.3kg	10.0kg
Solar Cell	Mono crystalline182*91mm, 132(6*22)		
Frame	/		
GLASS	/		
Junction Box	IP68,3diodes, MC4 compatible		
Output Cables	4.0mm ² (IEC),300mm(+)/300mm(-)or Customized Length		

Temperature characteristic

Pmax Temperature Coefficient	-0.35 %/° C
Voc Temperature Coefficient	-0.26 %/° C
Isc Temperature Coefficient	+0.047 %/° C
Operating Temperature	-40 ~ +85 ° C
Nominal module operation temperature	45 ± 2 ° C

Package

Packing Unit	40HQ	17.5m platform truck
PCS/CTNS	68	68
Qty of Package	20	32
PCS/Packages	1360	2176